


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 : F16H 7/08		A1	(11) International Publication Number: WO 00/57083
			(43) International Publication Date: 28 September 2000 (28.09.00)
(21) International Application Number: PCT/NL00/00188		(81) Designated States: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 21 March 2000 (21.03.00)			
(30) Priority Data: 1011625 22 March 1999 (22.03.99) NL			
(71) Applicant (for all designated States except US): SKF ENGINEERING AND RESEARCH CENTRE B.V. [NL/NL]; P.O. Box 2350, NL-3430 DT Nieuwegein (NL).			
(72) Inventors; and (75) Inventors/Applicants (for US only): KAPAAN, Hendrikus, Jan [NL/NL]; Waterhoen 5, NL-3435 DM Nieuwegein (NL). VAN WINDEN, Johannes, Albertus [NL/NL]; Molenwal 4, NL-3421 CM Oudewater (NL). HOLWEG, Eduardus, Gerardus, Maria [NL/NL]; Paradijspoort 44, NL-2611 MB Delft (NL).			
(74) Agent: JORRITSMA, Ruurd; Nederlandsch Octrooibureau, Scheveningseweg 82, P.O. Box 29720, NL-2502 LS The Hague (NL).		Published With international search report.	

(54) Title: METHOD FOR CONTROLLING A BELT-PULLEY DRIVE SYSTEM, AND BELT-PULLEY DRIVE SYSTEM

(57) Abstract

A method for controlling the tension in a belt-pulley drive system comprising at least one drive pulley and one driven pulley (1, 2, 3), around which a drive belt (4) is applied under tension, tensioning means (5, 6) for influencing said tension, and control means (10) for controlling the tensioning means (5, 6), comprises the steps of: determining the vibration in the drive system, or a parameter associated with the vibration behaviour thereof, controlling the tension in the drive belt on the basis of said vibrations, or the magnitude of said parameter.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

Method for controlling a belt-pulley drive system, and belt-pulley drive system

The invention is related to the field of belt-pulley drive systems, and in particular to the behaviour thereof under load. Belt pulley drive systems are applied
5 in several fields. As an example, the belt-pulley drive for driving the ancillary equipment of a combustion engine is mentioned, e.g. for driving the dynamo, water pump etcetera.

These drive systems operate within a range of rotational speeds, depending on e.g. the power required from a combustion engine. As a result of these varying
10 operating conditions, vibrations may develop in the belt-pulley drive system. Such vibrations also depend on the tension in the belt, and also the wear conditions of the belt-pulley drive system.

The occurrence of such vibration is undesirable, as they may cause damage to the drive system and may aggravate wear. Furthermore, the noise produced may be
15 unacceptable, e.g. in motor vehicle applications.

The object of the invention is therefore to provide a method for improving the behaviour of such drive system under load. This object is achieved by means of a method for controlling the tension in a belt-pulley drive system comprising at least one drive pulley and one driven pulley, around which a drive belt is applied under
20 tension, tensioning means for influencing said tension, and control means for controlling the tensioning means, said method comprising the steps of:

- determining the vibrations in the drive system, or a parameter associated with the vibration behaviour thereof,
- controlling the tension in the drive belt on the basis of said vibrations, or the
25 magnitude of said parameter.

After determining the vibrations in the drive system, it is possible to influence the belt tension in such a way that the vibrations are reduced or completely suppressed. This has the advantage that a standard pulley-belt drive system still can be used, while at the same time an upgrading of its vibration behaviour is obtained
30 by means of added-on control steps.

Additionally, other phenomena which influence the behaviour of a belt-pulley drive system can be taken into consideration as well. As an example, the undesirable occurrence of slip between the drive belt and the pulleys is mentioned.

Here as well, the invention may be applied in a fruitful way, by applying the steps of

- determining the slip between the drive belt and at least one of the pulleys,
 - controlling the tension in the drive belt also on the basis of the magnitude of
- 5 said slip.

Thus, according to the invention also slip, which contributes to the wear of the belt and pulleys, may be suppressed.

The method according to the invention can be put into practice in several ways. For instance, the method may be used in combination with a monitoring

10 system which detects vibration phenomena, as slip etcetera. The tension is then controlled on the basis of signals which are provided by the monitoring system.

Other practical applications for the method are possible as well. It should be borne in mind that in most cases, identical belt-pulley drive systems are applied in an identical environment, e.g. as ancillary component for a combustion engine. In such

15 cases, according to the invention the method according to the invention can be applied by:

- determining a control procedure for the belt tension in a test belt-pulley drive system,
 - establishing a relation between said control procedure and a characteristic of
- 20 said drive system,
- copying said control procedure in the control means of a nominal belt-pulley drive which system is identical to the test belt-pulley drive system,
 - controlling the nominal belt-pulley drive system on the basis of said same characteristic and said control procedure.

25 According to this variant of the method according to the invention, only one belt-pulley drive system need to be tested, and the subsequent production belt-pulley drive systems are then produced in a standard fashion.

The characteristics to be used in the method according to the invention may for instance comprise the engine speed, vibrations etcetera.

30 The invention is also related to a belt, wherein the tensioning means comprises an idle roller connected to an actuating means, said actuating being arranged for pressing the idle roller onto a part of the belt between the pulleys.

The tensioning means may for instance comprise an idle roller connected to an actuating means, said actuating being arranged for pressing the idle roller onto a part of the belt between the pulleys.

5 The invention will now be described further with reference to an embodiment shown in the figure.

The figure shows a belt-pulley drive system, comprising rollers 1, 2, 3, connected by a belt 4. The belt-pulley drive system may e.g. be applied in a combustion engine, for driving the dynamo and/or water pump.

10 A part of the belt 4 is influenced by a tension wheel 5, which is pressed towards said part of the belt 4 by means of a linear actuator 6. This actuator 6 is connected to a fixed point, e.g. to the engine in question.

Furthermore, a sensor 8 has been applied for detecting certain phenomena in the belt 4, in particular vibrations. The sensor 8 emits signals which are indicative of those vibrations, which signals by means of cable 9 are transmitted to the control unit
15 10. The sensor 8 may be integrated in the linear actuator 6.

The control unit 10 influences the linear actuator in such a way that by means of tension wheel 5 the belt tension is influenced so as to remove the vibrations.

The control unit may comprise a memory into which for instance a vibration spectrum of the belt is stored. This provides for a "self learning" capability of the
20 belt-pulley drive system. On the basis of these store data, the control unit automatically will influence the actuator, and thereby the tension wheel and the tensioning belt 4 in such a way, that future negative phenomena, e.g. vibrations, are damped and prevented at an early stage.

Claims

1. Method for controlling the tension in a belt-pulley drive system comprising at least one drive pulley and one driven pulley, around which a drive belt is applied
5 under tension, tensioning means for influencing said tension, and control means for controlling the tensioning means, said method comprising the steps of:

- determining the vibrations in the drive system, or a parameter associated with the vibration behaviour thereof,

- controlling the tension in the drive belt on the basis of said vibrations, or the
10 magnitude of said parameter.

2. Method according to claim 1, comprising the steps of

- determining the slip between the drive belt and at least one of the pulleys,
- controlling the tension in the drive belt also on the basis of the magnitude of

15 said slip.

3. Method according to claim 1 or 2, comprising the steps of:

- determining a control procedure for the belt tension in a test belt-pulley drive system,

- establishing a relation between said control procedure and a characteristic of
20 said drive system,

- copying said control procedure in the control means of a nominal belt-pulley drive which system is identical to the test belt-pulley drive system,

- controlling the nominal belt-pulley drive system on the basis of said same
25 characteristic and said control procedure.

4. Method according to claim 3, wherein the drive system comprises an engine connected to the driven pulley, and the characteristic is the engine speed.

30 5. Method according to any of the preceding claims, comprising the steps of:

- reducing a vibration spectrum of the drive system,

- controlling the tension in the drive belt on the basis of said recorded vibration spectrum

6. Method according to any of the preceding claims, comprising the steps of:

- storing the vibrations, or a parameter associated therewith, in a memory,
- controlling the tension in the drive belt also on the basis of the stored

vibrations or parameter.

5

7. Method according to any of claims 1-6, wherein the tensioning means comprise an on/off electromagnet providing a rest position and a tensioning position for increasing the drive belt tension.

10

8. Method according to any of claims 1-6, wherein the tensioning means comprise an actuator, e.g. a screw actuator and a rotational motor, or a linear motor.

9. Belt-pulley drive system, comprising at least two pulleys around which a drive belt is applied under tension, tensioning means for influencing said tension, control means for controlling the tensioning means, said control means controlling the tensioning means according to the method of any of claims 1-8.

15

10. Belt-pulley drive system according to claim 9, wherein the tensioning means comprises an idle roller connected to an actuating means, said actuating being arranged for pressing the idle roller onto a part of the belt between the pulleys.

20

11. Belt-pulley drive system according to claim 10, wherein the actuating means comprises a magnet for displacing the idle roller between an active position in engagement with a part of the belt, and an inactive position.


25

12. Belt pulley drive system according to claim 10, wherein the actuating means comprise a screw actuator, e.g. a screw actuator and a rotational motor, or a linear motor.

30

13. Belt-pulley drive system according to claim 6, 7 or 8, wherein the pulleys have a fixed diameter groove.

1/1



A. CLASSIFICATION OF SUBJECT MATTER
 IPC 7 F16H7/08

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 F16H

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	FR 2 705 750 A (ECA)	1
A	2 December 1994 (1994-12-02) abstract; figure 1	5,6,9-13
A	GB 2 219 657 A (LOUGHBOROUGH) 13 December 1989 (1989-12-13) page 2 -page 4	1,5,6, 9-13
A	US 4 478 595 A (NIPPONDENSO) 23 October 1984 (1984-10-23) column 1 -column 4; figure 1	1,7-13
A	US 5 752 891 A (FORD GLOBAL) 19 May 1998 (1998-05-19) abstract; figures 1,3	1,8-13
	-/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

*** Special categories of cited documents :**

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

Z document member of the same patent family

Date of the actual completion of the international search

5 June 2000

Date of mailing of the international search report

14/06/2000

Name and mailing address of the ISA

 European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3018

Authorized officer

Flores, E

INTERNATIONAL SEARCH REPORT

Inter national Application No

PCT/NL 00/00188

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 699 848 A (NSK) 6 March 1996 (1996-03-06) page 8; figure 7 -----	1,3,9-13

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
FR 2705750	A	02-12-1994	NONE	
GB 2219657	A	13-12-1989	WO 9015974 A	27-12-1990
US 4478595	A	23-10-1984	JP 57161344 A	04-10-1982
US 5752891	A	19-05-1998	CA 2171043 A	21-09-1996
			DE 19604182 A	26-09-1996
EP 0699848	A	06-03-1996	JP 8074953 A	19-03-1996
			DE 69506198 D	07-01-1999
			DE 69506198 T	15-04-1999
			KR 180345 B	01-04-1999
			US 5632698 A	27-05-1997